



# SECURE-TECH

DETENTION ELECTRONIC SYSTEMS  
ETECH CONTROLS CORPORATION - MANUFACTURER  
4051 ALVIS COURT #3, ROCKLIN, CALIFORNIA, USA 95677  
TEL (916) 630-1300 • FAX (916) 630-1100 • FREE (800) 800-2523

MODEL  
LED-

## METAL BEZEL TAMPER RESISTANT INDICATORS



LED-6MF

### 6mm Metal-Bezel Tamper-Resistant Indicators



LED-8MR

### 8mm Metal-Bezel Tamper-Resistant Indicators

### 10mm Metal-Bezel Tamper-Resistant Indicators



LED-10MH



LED-10MF

### 12mm Metal-Bezel Tamper Resistant Indicators



LED-12MH

LED-12MF-S  
(Screw Termination)

LED-12MF

Connection	TAB TERMINAL-PLUGGABLE
Dielectric Intensity	1100VAC
Ambient Temperature	-20° ~ +85° C
Panel Thickness	1 ~ 10 MM
Nut Torque	5 ~ 14 Nm
Protection Level	IP67, IK10
Lens	POLYCARBONATE
Enclosure	NICKEL PLATED BRASS/STAINLESS STEEL
Base	PA66 NYLON
Rated Current	20mA
LED Life	40,000 HOURS

## Secure-Tech.com offers several options for Tamper-Resistant, Metal Bezel LEDs

Secure-Tech.com Tamper Resistant Metal Bezel LED Indicators are available in 6mm (1/4") through 12mm (1/2") diameter for your High-Security or Detention Control Panel Project. Available in high-brightness Red, Green, Yellow, Blue and White, all Secure-Tech Tamper-Resistant LED Indicators have the following minimum features:

1. Tamper and break resistant Metal Indicator Bezels (typically nickel plated brass)
2. Environmental IP-67 rating (protected from dust and capable of withstanding water immersion between 15 cm and 1 meter for 30 minutes).
3. Utilize quick-connect screw or pluggable-tab type terminations. Pluggable female-spade to tab terminations are factory connected using mil-spec crimpers and insulated connectors.
4. 40,000 Hours MTBF Average Lifespan.
5. Available in 12vdc or 24vdc versions.
6. 2 YEAR WARRANTY